


Technical Data Sheet RoHS Compliant Product

EE14.2/4.7/7.2, No Gap Core, MnZn

Product Specifications:

Parameter		Symbol	Unit	Value	Geometry Drawing Reference
Magnetic Characteristics	Effective Length	l_e	mm	25.20	
	Effective Area	A_e	mm ²	25.40	
	Effective Volume	V_e	mm ³	641.20	
Dimensions	A	-	mm	14.20 ±0.30	
	B	-	mm	4.65 ±0.30	
	C	-	mm	7.20 ±0.20	
	D	-	mm	3.00 ±0.30	
	E	-	mm	10.20 min	
	F	-	mm	3.45 ±0.20	
	A – A'	-	mm	≤ 0.20	
Appx. Weight/Set	Weight	W	gm	3.03	

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc. as per IEC 63093 - 8

Inspection Criteria: IEC 60424, Guide on the limits of Surface Irregularities

Mechanical Strength: IEC 61631 Compliant

Compliant: RoHS & REACH

Test Conditions: 1 kHz/300 mV, Coil - N=100 Turns, 25°C

Power Loss Conditions: 100 kHz, 200 mT, 100°C

Material Grade	Initial Permeability (μ_i)	AL Value (nH/Set)	PV (W/Set)
SFP4	2300 ±25%	1700 ±25%	≤ 0.47
SFP95	3300 ±25%	2800 ±25%	≤ 0.40
SFA05	5000 ±25%		
SFA07	7000 ±25%		
SFA10	10000 ±30%		
SFA12	12000 ±30%		

Other AL values/air gaps and materials available on request