


Technical Data Sheet RoHS Compliant Product

ET20/20/04, MnZn

Product Specifications:

Parameter		Symbol	Unit	Value	Geometry Drawing Reference
Magnetic Characteristics	Effective Length	I_e	mm	52.1	
	Effective Area	A_e	mm ²	17.6	
	Effective Volume	V_e	mm ³	917.0	
Dimensions	A	-	mm	20.10 ± 0.40	
	B	-	mm	20.10 ± 0.40	
	C	-	mm	4.40 ± 0.20	
	D	-	mm	4.00 ± 0.20	
	E	-	mm	15.70min.	
	F	-	mm	15.70min	
	A - A'	-	mm	≤ 0.20	
Appx. Weight/Set	Weight	W	gm	3.88	

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc. as per IEC 63093 - 8

Inspection Criteria: IEC 60424, Guide on the limits of Surface Irregularities

Mechanical Strength: IEC 61631 Compliant

Compliant: RoHS & REACH

Test Conditions: 1 kHz/300 mV, Coil - N=100 Turns, 25°C

Power Loss Conditions: 100 kHz, 200 mT, 100°C

Material Grade	Initial Permeability (μ_i)	AL Value (nH/Set)	PV (W/Set)
SFP4	2300 ±25%		
SFP95	3300 ±25%		
SFA05	5000 ±25%		
SFA07	7000 ±25%	3100 ±25%	
SFA10	10000 ±30%	4400 ±25%	
SFA12	12000 ±30%	4850 ±25%	

Other AL values/air gaps and materials available on request